

METRIC ISO TUBE 304L AND 316L

OD	Weight per metre (kg) for given Wall Thickness in mm		
	1.5mm	2.0mm	3.0mm
28	0.99		
38	1.37		
43	1.56		
44.5		2.13	
53	1.93		
54		2.40	
69		3.35	
83	3.06		
84		3.90	
103	3.81		
104		5.12	
129		6.36	
153	5.69		
154		7.61	
204		10.12	
(206)			15.25
254		15.79	
256			19.01
304		15.12	
(355.6)			26.49
406.4			30.30
(508)			37.94
(609.6)			45.57

METRIC WELDED TUBE



Sizes in brackets are currently available in 304L only.

The Metric Fittings Range Includes

- 45° & 90° Elbows – Radius D+100
- 45° & 90° Elbows – Radius 1.5D
- Pulled Equal Tees
- Pulled Reducing Tees
- Concentric Reducers
- Eccentric Reducers
- Pressed Collars
- Pressed End Caps
- Mild Steel Backing Flanges – Zinc Plated

Weights

All weights shown in this publication are for guidance only. They are calculated using nominal dimensions and are scientifically recognised densities. Please note that in practice, the actual weight can vary significantly from the theoretical weight due to variations in manufacturing tolerances and compositions.

The information contained herein is based on our present knowledge and experience and is given in good faith. However, no liability will be accepted by the Company in respect of any action taken by any third party in reliance thereon.

As the products detailed herein may be used for a wide variety of purposes and as the Company has no control over their use, the Company specifically excludes all conditions and warranties expressed or implied by statute or otherwise as to dimensions, properties and/or their fitness for any particular purpose. Any advice given by the Company to any third party is given for that party's assistance only and without any liability on the part of the Company.

Any contract between the Company and the customer will be subject to the Company's Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available on request.

